

# ASL6101R-B ASL6101K-B ASL6101S-B

Bluetooth smart lock



## Features

- 4-way opening: Easy4key App, Mifare Card, password and mechanical key
- Voice prompt: All settings can be finished by following voice prompt
- Privacy password: xxx+password+xxx, preventing password to be seen by others
- Passage Mode and Non-disturbance Mode optional
- Auto lock when come across a consecutive invalid passwords or cards
- Low Voltage alarm( $\leq 4.5V$ ), doorbell
- Huge storage: 50 cards, 50 passwords
- Emergency power supply outside
- Three colors optional
- Zinc alloy material

## Technical Specification

### Card

Card Type	Mifare 1
Card Features	Contactless, high security, all-in-one possible
Sensor Distance	< 20mm
Sensor Time	< 0.5s
Storage Capacity	50

### Password

Keyboard Type	All-touch keyboard
Password Length	6-12 bits
Storage Capacity	50

### Battery

Working Voltage	6V, "AA"battery (4pcs)
Battery Life	About 1 year (10 units/D)
Low Battery Warning	< DC4.5V
Emergency Power Supply	9V battery

## Structure

Door Thickness	40-55mm (customizable)
Backset	62mm
Central Distance	97mm
Product Standard	GA374-2001(e-lock)
Material	Zinc alloy

## General

Working Temperature	-30°C~+70°C
Relative Humidity	10%~93%
Salt spray test	$\geq 200h$
Lock case test	$\geq 100000$ times
Package size	410*235*165(mm)
Gross weight	4.7kg
Restore Default	Support
Reset	Support
Ring	Support
Built-in Buzzer	Support
Built-in Loudspeaker	Support

Black Bronze

DHI-ASL6101K-B

Antique Copper

DHI-ASL6101R-B

Satin Silver

DHI-ASL6101S-B

Dimensions

